

# INT-TSI-WSW

## TOUCHSCREEN KEYPAD

The **INT-TSI** keypad is a real command center for a smart alarm system. As its interface can be customized to individual user's needs, it provides a perfect solution both for people expecting ease of operation and for advanced users who make use of the extended system functionality.

- capacitive glass touchscreen with 7" LCD
- graphic operating interface, customizable to individual user's needs
- an option to choose from a few graphics design
- MACRO functionality to implement a sequence of actions using a single button
- capability of viewing images from IP cameras (MJPG via HTTP and in v1.04: MPEG-4, H.264 via RTSP)
- an additional keypad can be connected via Ethernet to each keypad connected to the bus – which makes it possible to double the number of keypads in the system
- wide range of dedicated widgets for various functions, including weather widget to which forecast is downloaded from the **openweathermap.org** service
- scalability of the widget size
- capability to present the system state in the screensaver mode
- photo frame function
- capability of saving the user interface configuration directly from **TSI Builder** program to keypad over Ethernet



### TECHNICAL DATA

Supply voltage	12 V DC
Operating temperature range	-10°C...+55°C
Standby mode current consumption	500 mA
Max. current consumption	620 mA
Weight	430 g
Maximum humidity	93±3%
Environmental class according to EN50130-5	II
Supported memory cards	microSD, micro SDHC
Enclosure dimensions (width x height x thickness)	196 x 129 x 22 mm

