

INT-TSI-B

TOUCHSCREEN KEYPAD

The **INT-TSI** keypad is a real command center for a smart alarm system. As its interface can be customized to individual user's needs, it provides a perfect solution both for people expecting ease of operation and for advanced users who make use of the extended system functionality.

- capacitive glass touchscreen with 7" LCD
- graphic operating interface, customizable to individual user's needs
- an option to choose from a few graphics design
- MACRO functionality to implement a sequence of actions using a single button
- capability of viewing images from IP cameras (MJPG via HTTP and in v1.04: MPEG-4, H.264 via RTSP)
- "Intercom" widget - video intercom functionality; cooperation with door stations supporting the SIP protocol
- an additional keypad can be connected via Ethernet to each keypad connected to the bus - which makes it possible to double the number of keypads in the system
- wide range of dedicated widgets for various functions, including weather widget to which forecast is downloaded from the openweathermap.org service
- scalability of the widget size
- capability to present the system state in the screensaver mode
- photo frame function
- capability of saving the user interface configuration directly from **TSI Builder** program to keypad over Ethernet
- available in white (**INT-TSI-W**) and black (**INT-TSI-B**)



The operation of the "Intercom" widget in the INT-TSI keypad working with door stations supporting the SIP protocol was checked on various test sets. The best results were obtained with the following door station models:

- 2N IP Solo - firmware version 2.44.1.57.4
- 2N IP Force - firmware version 2.44.0.57.3
- 2N IP One - firmware version 2.44.0.57.3
- 2N IP Style - firmware version 2.44.0.57.3
- 2N IP Base - firmware version 2.40.0.53.4
- 2N IP Verso - firmware version 2.41.0.54.3
- Akuvox R20A - firmware version 320.30.3.125
- Akuvox R20BX2 - firmware version 220.30.3.7
- Akuvox R20K - firmware version 220.30.1.102

TECHNICAL DATA

| | |
|---|---------------------|
| Supply voltage | 12 V DC |
| Operating temperature range | -10°C...+55°C |
| Standby mode current consumption | 500 mA |
| Max. current consumption | 620 mA |
| Weight | 430 g |
| Maximum humidity | 93±3% |
| Environmental class according to EN50130-5 | II |
| Supported memory cards | microSD, micro SDHC |
| Enclosure dimensions (width x height x thickness) | 196 x 129 x 22 mm |

