

# SPW-220 R

## INDOOR SIREN WITH OPTICAL AND ACOUSTICAL SIGNALING

SPW-220 R is a siren with optical and acoustic signaling, designed for indoor installation and provided with super-bright LEDs and piezoelectric transducer. The two optical sets placed on the sides of the enclosure make the light alarm of the device perfectly visible even from a large distance, also in daylight. It offers three types of 120 dB intensity modulated tones to choose from. The loud signal ensures good audibility over a large area, e.g. in warehouses, production halls, parking lots inside buildings, etc. Enclosure of the siren is made of polycarbonate, thus ensuring high mechanical strength and aesthetic appearance of the device that remains unchanged over time. The siren is provided with tamper protection against opening or tearing off the wall.

The SPW-220 optical-acoustic siren is available in two color versions: SPW-220 R (red) and SPW-220 BL (blue).

- acoustical signaling: piezo transducer
- optical signaling: ultra bright LEDs
- tamper protection against opening and removing from mounting surface
- available also in blue (**SPW-220 BL**)

## TECHNICAL DATA

Environmental class	II
Supply voltage	12 V DC
Enclosure dimensions	87 x 133 x 37 mm
Operating temperature range	-10...+55 °C
Weight	199 g
The intensity of sound	120 dB
Maximum current consumption - optical signaling	200 mA
Maximum current consumption - acoustic signaling	110 mA
Maximum current consumption - optical and acoustic signaling	300 mA