

## B-1T BR

## SURFACE-MOUNTED MAGNETIC CONTACT WITH TERMINALS (BROWN)

Magnetic contacts constitute basic elements of perimeter protection systems and their primary task is to detect attempts of opening doors and windows. Medium–size **B–1T BR** magnetic contacts are designed for surface mounting and equipped with connection terminals. They can only be mounted by screwing them to a surface. The contacts are available in white and brown colour versions.

- surface mounted (screw mount)
- medium sized sealed body



## **TECHNICAL DATA**

Max. switched current         500 μA           Operating temperature range         -10+55 ° C           Weight         18 g           Maximum humidity         93±3%           Make distance         25 mm           Break distance         30 mm           Dimensions magnet enclosure         65,5 x 11,1 x 13,6 mm           Environmental class according to EN50130-5         II           Detector type (outside magnetic field)         NO		
Operating temperature range         -10+55 ° C           Weight         18 g           Maximum humidity         93±3%           Make distance         25 mm           Break distance         30 mm           Dimensions magnet enclosure         65,5 x 11,1 x 13,6 mm           Environmental class according to EN50130-5         II           Detector type (outside magnetic field)         NO	Max. reed switched voltage	100 V DC
Weight         18 g           Maximum humidity         93±3%           Make distance         25 mm           Break distance         30 mm           Dimensions magnet enclosure         65,5 x 11,1 x 13,6 mm           Environmental class according to EN50130-5         II           Detector type (outside magnetic field)         NO	Max. switched current	500 μA
Maximum humidity         93±3%           Make distance         25 mm           Break distance         30 mm           Dimensions magnet enclosure         65,5 x 11,1 x 13,6 mm           Environmental class according to EN50130-5         II           Detector type (outside magnetic field)         NO	Operating temperature range	-10+55 °C
Make distance         25 mm           Break distance         30 mm           Dimensions magnet enclosure         65,5 x 11,1 x 13,6 mm           Environmental class according to EN50130-5         II           Detector type (outside magnetic field)         NO	Weight	18 g
Break distance 30 mm  Dimensions magnet enclosure 65,5 x 11,1 x 13,6 mm  Environmental class according to EN50130-5 II  Detector type (outside magnetic field) NO	Maximum humidity	93±3%
Dimensions magnet enclosure 65,5 x 11,1 x 13,6 mm  Environmental class according to EN50130-5 II  Detector type (outside magnetic field) NO	Make distance	25 mm
Environmental class according to EN50130-5 II  Detector type (outside magnetic field) NO	Break distance	30 mm
Detector type (outside magnetic field)  NO	Dimensions magnet enclosure	65,5 x 11,1 x 13,6 mm
	Environmental class according to EN50130-5	II
Reed switch enclosure dimensions 65,5 x 11,1 x 13,6 mm	Detector type (outside magnetic field)	NO
	Reed switch enclosure dimensions	65,5 x 11,1 x 13,6 mm

