

MSP-300 R

WIRELESS OUTDOOR ACOUSTIC AND OPTICAL SIREN

The MSP-300 wireless outdoor siren is designed to work in conjunction with **PERFECTA** control panels (equipped with **PERFECTA-RF** module or **WRL** models) and **MTX-300** controller, operating at 433 MHz frequency. The modern SPIRIT1 radio system with optimized power management, which enables long-lasting operation of the device in harsh environments, has been used in the siren. Trouble-free functioning of the MSP-300 is also possible due to the **BAT-ER-3,6** high-performance battery, which is used in specialized applications, including military and medical ones.

The **MSP-300** siren is available in two colours: red (**MSP-300 R**) blue (**MSP-300 BL**).

- compatible with **PERFECTA** (equipped with **PERFECTA-RF** module or **WRL** models) control panels as well as **MTX-300** controller
- independent wireless triggering of optical and acoustic signals
- optical signaling: ultra bright LEDs
- acoustic signaling: piezoelectric transducer
- several acoustic signals to choose from
- advanced radio system for optimized low power communication
- remote configuration
- powered from **BAT-ER-3,6**, 13 Ah, wide temperature range, high-performance battery
- operating temperature from -40°C to $+55^{\circ}\text{C}$
- tamper protection against enclosure opening / tear-off
- also available in colour blue (**MSP-300 BL**)



TECHNICAL DATA

Battery working time (in years)	up to 3
Operating temperature range	-40°C ... $+55^{\circ}\text{C}$
Standby mode current consumption	600 μA
Max. current consumption	500 mA
Weight	766 g
Maximum humidity	93 \pm 3%
Operating frequency band	433,05 \div 434,79 MHz
Radio communication range (in open area)	up to 400 m
Battery	ER34615 3,6V
Dimensions	148 x 254 x 64 mm
Environmental class according to EN50130-5	IIIA
Sound pressure level at 1m	up to 105 dB

