

ASP-105 R

WIRELESSLY TRIGGERED OUTDOOR SIREN

ASP-105 is a wirelessly triggered acoustic-optical siren, designed for outdoor installation, which due to the use of impregnated electronic circuitry is immune to the effect of atmospheric conditions. The siren is designed to work as part of the **ABAX** two-way wireless system. It is provided with ultra bright LEDs and acoustic transducer to ensure a loud alarm. You can choose one of four modulated sounds with an intensity of 120 dB. Optical and acoustic signals can be triggered independently by radio. Configuration of the device parameters is performed remotely using the **DLOADX** program. ASP-105 is powered from an external 12 V DC voltage source and has a built-in backup battery (6 V, 1.2 Ah). Tamper switch protects the device against opening the enclosure or tearing off the wall. The siren meets the EN 50131-4 security requirements for Grade 2.

ASP-105 is available in three color versions: red (**ASP-105 R**), blue (**ASP-105 BL**) and orange (**ASP-105 O**).

- wireless triggering of optical and acoustical signaling
- optical signaling: ultra bright LEDs
- selection of four acoustic signals
- remote configuration
- long-lasting rechargeable battery powered by external power supply
- tamper protection:
 - against opening
 - against removing from mounting surface
- available also in blue (**ASP-105 BL**) and orange (**ASP-105 O**)

TECHNICAL DATA

Built-in battery	6 V 1,2 Ah
Supply voltage	12 V DC
Enclosure dimensions	148 x 254 x 64 mm
Operating temperature range	-25...+70 °C
Standby mode current consumption	30 mA
Weight	1010 g
The intensity of sound	up to 120 dB
Maximum humidity	93 ±3%
Operating frequency band	868,0 ÷ 868,6 MHz
Radio communication range (in open area)	up to 500 m
Environmental class according to EN50130-5	IV
Complied with standards	EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-4, EN 50131-5-3
Maximum current consumption - optical signaling	80 mA
Maximum current consumption - acoustic signaling	225 mA
Maximum current consumption - optical and acoustic signaling	265 mA
Security grade according to EN 50131-4	Grade 2
Name of certification body	Telefication

